

LW-2402 FULL HD DESKTOP MONITOR




FEATURES


- Full HD 1920 x 1080 resolution
- 178°/ 178° (H/V) wide viewing angle
- 20,000,000:1 contrast ratio and 250 nits brightness
- Both VGA and HDMI inputs
- Integrated dual 1W speakers
- Flicker-free and blue light filter eye-care technology
- Compatible with VSEA 100 x 100mm mounting


The LW-2402 24-inch Full HD desktop monitor provides essential needs for daily work at home and office. Featuring Full HD 1920 x 1080 resolution, 178/178 degrees wide viewing angle, a 20,000,000:1 contrast ratio, and both HDMI and VGA inputs, the monitor can deliver decent image performance from notebook or PC. With flicker-free technology and a blue-light filter technology, the LW-2402 can reduce eye strain during a long period of time while working on spreadsheets or viewing multimedia content.

TECHNICAL DRAWING
















SPECIFICATIONS

Panel

Panel Type
Panel Size
Max. Resolution
Pixel Pitch
Brightness
Contrast Ratio
Viewing Angle (H/V)
Display Colour
Response Time
Surface Treatment
Frequency
Frequency (H)
Frequency (V)
Signal Input
HDMI
VGA
Audio
Audio In
Internal Speakers
Power
Power Requirements
On Mode
Standby Mode
Off Mode
Power Supply
Operating Conditions
Temperature
Humidity
Storage Conditions
Temperature
Humidity
Mounting
VESA FPMPMI
Stand
Tilt
Security
Kensington Security Slot
Dimensions
Product with Base (W x H x D)
Product w/o Base (W x H x D)
Packaging (W x H x D)
Weight
Product w/o Base
Product with Base
Packaging
Regulation Approval
Certifications & Compliance
Power Adaptor Certifications
Accessories

Accessories

Supplied Optional Accessories Ceiling Mount (Landscape only) Wall Mount (Landscape only) Desk mount (Landscape only)

LED-Backlit TFT LCD (VA Technology)
23.8"
FHD 1920 x 1080
0.275 mm
250 cd/m ²
20,000,000 (DCR)
178°/178°
16.7M 5 ms
Anti-Glare Treatment (Haze 25 %), 3H Hard Coating
Anti-Glare Treatment (Traze 25 %), Sh hard Coating
30 to 81KHz
48 to 75Hz
1.4 x 1
15 -pin D-SUB
Stereo Audio Jack (3.5 mm)
1 W x 2
DC 12V, 2.5A
15.5W (On)
< 0.5W
< 0.3W
External
0°C-40°C (32°F-104°F)
20%-85% (non-condensing)
-20°C-60°C (-4°F-140°F)
5%-95% (non-condensing)
Yes (100 x 100 mm)
-5° to 15°
Yes
565.3 x 430.0 x 180.8 mm (22.3" x 16.9" x 7.1")
565.3 x 335.0 x 53.7 mm (22.3" x 13.2" x 2.1")
627.0 x 397.0 x 128.0 mm (24.7" x 15.6" x5.0")
2.4 kg (5.3 lb)
2.8 kg (6.2 lb)
4.2 kg (9.3 lb)
CE, LVD, WEEE, RoHS, REACH, UKCA
Honor/ ADS-40NP-12-1 12030E: CE, cUL/UL, PSE, RCM, WEEE, KCC, BSMI, EAC, UKCA
Power Adaptor, Power Cord, HDMI Cable, Quick Start Guide, Warranty Card

CMP-01+WMK-03 WMA-01, WMK-01, WMK-03, PMK-01 DMC-01, DMC-02D, DMS-01D, ES-02













All specifications are subject to change without prior notice. Copyright © 2022 AG Neovo. All rights reserved. The name AG Neovo is a trademark of AIC. All other trademarks are the property of their respective owners. P/C: LW2420 Version 1.1, 20220510

www.agneovo.com