

Data Sheet

FUJITSU Display E24-9 TOUCH

Multi-touch 60.5 cm (23.8-inch) Ergonomic Display for touch-based application scenarios

The FUJITSU Display E24-9 TOUCH is a 10 point projected capacitive touch (PCT) ergonomic display with 1920 x 1080 Full HD resolution. The monitor screen comes with anti-glare that helps prevent smudges, spots and blurs owing to touch-intensive tasks. It also has powerful built-in speakers and a range of interfaces for easy connectivity and maximum flexibility.

23.8-inch multi-touch display with FHD resolution providing consistent clarity and superior viewing experience, ideal for touch-based applications

Full metal non-gliding photo frame-type stand that enables users to transition from normal desktop viewing angle to extended tilt (+10° to +65°) for touch-based applications

Ultra-thin bezel housing with an anti-glare treatment that enables users to swipe, tap, slide and pinch for a smudge- as distraction-free working experience

Flexible connectivity with DisplayPort, HDMI and USB 3.1 interfaces, paired with integrated speakers for a complete business package

Environmental-friendly LED technology with highly efficient energy saving functions like ECO Operation mode and ECO standby helping you save on costs



Technical details

Special features

	Touch technology with projected capacitive touch (PCT) and 10-finger system with anti-glare treatment, In-Plane Switching (IPS) technology, Eco button for Eco mode and 3-coloured Eco status LED, Integrated speakers
--	--

Stand	non-gliding metal photo stand
-------	-------------------------------

Tilt angle	+10° / +65°
------------	-------------

Picture performance

Panel and backlight	In-Plane Switching (IPS) technology/LED
---------------------	---

Screen Surface Treatment	Anti-glare, 3H hard coating
--------------------------	-----------------------------

Contrast - typical	1,000:1
--------------------	---------

Contrast - advanced	20,000,000:1
---------------------	--------------

Response time gray to gray typical	5 ms (in video mode)
------------------------------------	----------------------

Viewing angle (h/v) - typical	178°/178° CR10:1
-------------------------------	------------------

Color performance	16.7 million colors (Hi-FRC)
-------------------	------------------------------

Brightness - typical	250 cd/m ²
----------------------	-----------------------

Size and resolution

Aspect ratio	16:9
--------------	------

Diagonal Size	60.5 cm (23.8-inch)
---------------	---------------------

Resolution (native)	1,920 x 1,080 pixel
---------------------	---------------------

Resolution (interpolated)	1,680 x 1,050 pixel, 1,440 x 900 pixel, 1,280 x 1,024 pixel, 1,280 x 720 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
---------------------------	---

Picture size	527 x 296 mm
--------------	--------------

Pixel Pitch	0.2745 mm
-------------	-----------

Frequencies

Horizontal	30 - 82 kHz
------------	-------------

Vertical	56 - 76 Hz
----------	------------

Connectivity

DisplayPort	1 x DisplayPort
-------------	-----------------

HDMI	1 x HDMI
------	----------

VGA/D-SUB	1 x D-SUB
-----------	-----------

Audio signal output	3.5 mm stereo phone jack for head phone
---------------------	---

Audio sound output	2 x 2 W
--------------------	---------

Audio signal input	3.5 mm stereo phone jack
--------------------	--------------------------

USB downstream	2x USB 3.1 (Gen1)
----------------	-------------------

USB upstream	1 x USB 3.1 (Gen1)
--------------	--------------------

Ease-of-use menu

Direct Access Keys	Brightness, ECO, Input, Mode, Audio, Menu
--------------------	---

Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
-----------	---

Brightness / Contrast	Brightness, Contrast, Black level, Auto level, ACR
-----------------------	--

Mode	sRGB, Office, Photo, Video, Low Blue Light
------	--

Color	sRGB, 5000K, 6500K, 7500K, Native, Custom Color (R,G,B)
-------	---

OSD	Language, OSD-Timeout, OSD rotation
-----	-------------------------------------

Image adjust	Clock, Phase, H-Position, V-Position, Expansion
--------------	---

Audio	Mute, Volume, Input for HDMI and DP interface
-------	---

Information	Model name, Serial number, Signal input, Resolution/mode, Display mode, Color Temperature, ACR Status
-------------	---

Advanced settings	Overdrive, DDC/CI, Factory Recall
-------------------	-----------------------------------

Power consumption (typical, w/o sound)

Soft switch off	0.12 W
-----------------	--------

Power save mode	0.15 W
-----------------	--------

Operating with EPA settings	15.25 W
-----------------------------	---------

Total Energy Consumption (ETEC)	47.6 kWh/year
---------------------------------	---------------

Operating maximum brightness	23 W
Power supply	integrated
Power notes	Speakers off, USB not connected ETEC and EPA refer to ENERGY STAR® 8.0
Electrical values	
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
Compliance	
Product	E24-9 TOUCH
Model	E24-9 TOUCH
Global	TCO Certified Displays 8.0, ENERGY STAR® 8.0, EPEAT® Bronze (dedicated regions), TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I)
Europe	EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration
Australia/New Zealand	(on customer request)
China	CCC
Germany	TÜV GS
India	BIS
Russia	EAC
Singapore	S-Mark
South Korea	KC
Taiwan	BSMI
USA/Canada	FCC Class B, cTUVus
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	540.3 x 63.5 x 325.6 mm 21.27 x 2.5 x 12.82 inch
Dimension with stand (W x D x H)	540.3 x 107.35 x 325.6 mm 21.27 inch x 4.23 x 12.82 inch
Weight (unpacked)	3.8 kg 8.38 lbs
Weight (Monitor only)	3.3 kg 7.28 lbs
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Operating relative humidity	10 - 85 % (non condensing)
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Black
Package content	
Display delivered accessories	DisplayPort data cable 1.8 m USB-cable 1.8 m (USB-A to USB-B) Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Safety notes
Display delivered accessories notes	Power cable with IEC-60320-C13, 3-pin connector on display side Data cables and USB cable detachable on display User manual is available via download
Packaging dimension (mm)	
Weight (packed)	5.3 kg
Weight (packed) (lbs)	11.68 lbs
Order information	
Order Code	S26361-K1644-V160
EAN Code	4059595400562

Order information

Country specific order code	BDL:K1644V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1603V160-CHN - with China power cable and CEL, mandatory for China BDL:K1644V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed, on demand
-----------------------------	---

Warranty

Warranty period	3 years (depending on country)
Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Spare Parts availability	7 years after end of product life
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

More information

Fujitsu products, solutions & services

In addition to FUJITSU Display E24-9 TOUCH, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Display E24-9 TOUCH, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/emeia/products/computing/peripheral/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>

Copyright 2021 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com
2021-05-17 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>
Copyright 2021 Fujitsu Technology Solutions GmbH