

## Key **Features**

- Ergonomic flexibility with quick-release
   stand
- vDisplay Manager productivity software for maximized multitasking
- Dual front facing speakers for clear audio
- HDMI, DisplayPort, VGA, and USB3.2 ports for extended connectivity
- 3-Sided narrow bezel for uninterrupted viewing



## Product **Description**

The ViewSonic VG2440 is a 24" Full HD ergonomic business monitor designed to increase productivity and efficiency within the home and office workspace. Providing the full spectrum of ergonomic flexibility, the VG2440 can tilt, swivel, pivot, and height adjust to adapt to any setup or workflow, while the built-in vDisplay Manager productivity software delivers efficient multi-tasking ability and streamlined display control. Dual front-facing speakers ensure a perfect audio-visual experience to provide teams with quality remote communication and collaboration. The beautifully designed display includes a 3-sided narrow bezel for uninterrupted viewing in multi-monitor display setups as well HDMI. DisplayPort, VGA, and USB3.2 connectivity. Complete with an easy-to-install quick release stand that reduces setup time to only a few minutes, the VG2440 offers a high-performance, purpose-built display solution designed for workspace productivity.



Visit Us www.viewsonic.com

DISPLAY		INPUT SIGNAL	
Display Size (in.):	24	<b>.</b>	RGB Analog: 16 ~ 83KHz, HDMI
Viewable Area (in.):	23.6	Frequency Horizontal:	(v1.4): 15 ~ 90KHz, DisplayPort (v1.2): 15 ~ 90KHz
Panel Type:	VA Technology		RGB Analog: 50 ~ 75Hz, HDMI
Resolution:	1920 x 1080	Frequency Vertical:	(v1.4): 49 ~ 75Hz, DisplayPort (v1.2): 49 ~ 75Hz
Resolution Type:	FHD (Full HD)	VIDEO INPUT	
Static Contrast Ratio:	3,000:1 (typ)	Digital Sync:	TMDS - HDMI (v1.4), PCI-E -
Dynamic Contrast Ratio:	80M:1		DisplayPort (v1.2)
Light Source:	LED	Analog Sync:	Separate/Composite/SOG - RGB Analog
Brightness:	250 cd/m² (typ)	ERGONOMICS	
Colors:	16.7M	Height Adjust (mm):	130
Color Space Support:	8 bit (6 bit + Hi-FRC)	Swivel:	120°
Aspect Ratio:	16:9	Tilt (Forward/Back):	-5° / 40°
Response Time (Typical GTG):	5ms	Pivot (Right/Left):	90° / 90°
Response Time (GTG w/OD):	5ms	WEIGHT (IMPERIAL)	
Viewing Angles:	178° horizontal, 178° vertical	Net (lbs):	12.9
Backlight Life (Hours):	30000 Hrs (Min)	Net Without Stand (lbs):	7.5
Curvature:	Flat	Gross (lbs):	18.7
Refresh Rate (Hz):	60	WEIGHT (METRIC)	
Blue Light Filter:	Yes	Net (kg):	5.8
Flicker-Free:	Yes	Net Without Stand (kg):	3.4
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104%	Gross (kg):	8.5
	size (Typ)	DIMENSIONS (IMPERIAL) (W	•
Pixel Size:	0.272 mm (H) x 0.272 mm (V)	Packaging (in.):	24 x 15.9 x 8.3
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Physical (in.):	21.6 x 15.12~20.22 x 8.1
COMPATIBILITY	4000::4000	Physical Without Stand (in.):	21.6 x 12.9 x 2
PC Resolution (max):	1920x1080	DIMENSIONS (METRIC) (WXI	
Mac® Resolution (max):	1920x1080	Packaging (mm):	609 x 405 x 210
PC Operating System:	Windows 7/8/8.1/10/11 certified; macOS tested	Physical (mm):	549 x 384.07~513.58 x 206
Mac® Resolution (min):	1920x1080	Physical Without Stand (mm):	549 x 329 x 50
CONNECTOR		GENERAL	
VGA:	1	Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 8.0, EAC,
USB 3.2 Type A Down Stream:	4		
USB 3.2 Type B Up Stream:	1		UkrSEPRO, UKCA
3.5mm Audio In:	1		VG2440 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male- Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Audio Cable (Male-
3.5mm Audio Out:	1	PACKAGE CONTENTS:	
HDMI 1.4:	1		Male) x1, Quick Start Guide x1
DisplayPort:	1	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Power in:	3-pin Socket (IEC C14 / CEE22)		*Warranty offered may differ from
AUDIO		Warranty:	market to market
Internal Speakers:	2Watts x2	Power Management:	Energy Star standards, EPEAT
POWER			
Eco Mode (Conserve):	11.81W		
Eco Mode (optimized):	13.08W		
Consumption (typical):	14.85W		
Consumption (max):	16.24W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:			
Tower Suppry.	Internal Power Supply		
ADDITIONAL HARDWARE			
ADDITIONAL HARDWARE  Kensington Lock Slot:	1		
ADDITIONAL HARDWARE Kensington Lock Slot: Cable Organization:			
ADDITIONAL HARDWARE  Kensington Lock Slot:	1 Yes		
ADDITIONAL HARDWARE Kensington Lock Slot: Cable Organization:	1 Yes Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power)		
ADDITIONAL HARDWARE Kensington Lock Slot: Cable Organization: CONTROLS	1 Yes Key 1 (eye), Key 2, Key 3, Key 4,		
ADDITIONAL HARDWARE Kensington Lock Slot: Cable Organization: CONTROLS Physical Controls:	1 Yes  Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power)  Input Select, Audio Adjust, ViewMode, Color Adjust, Manual		
ADDITIONAL HARDWARE Kensington Lock Slot: Cable Organization: CONTROLS Physical Controls: On Screen Display:	1 Yes  Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power)  Input Select, Audio Adjust, ViewMode, Color Adjust, Manual		
ADDITIONAL HARDWARE Kensington Lock Slot: Cable Organization: CONTROLS Physical Controls: On Screen Display: OPERATING CONDITIONS Temperature: Humidity (non-condensing):	1 Yes Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
ADDITIONAL HARDWARE Kensington Lock Slot: Cable Organization: CONTROLS Physical Controls: On Screen Display: OPERATING CONDITIONS Temperature:	1 Yes Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu  32°F to 104°F (0°C to 40°C)		

Copyright © ViewSonic Corporation 2000-2022. All rights reserved.