

⊖ PANEL

| | |
|---|---|
| Screen Size 49" (123cm) | Panel Technology IPS |
| Aspect Ratio 16:9 | Native Resolution 1,920 x 1,080 (FHD) |
| Brightness (Typ.) 450 cd/m ² | Contrast Ratio 1,300:1 |
| Dynamic CR 500,000:1 | Viewing Angle (H x V) 178 x 178 |
| Colour Depth 1.07 Billion | Response Time 8 ms (G to G) |
| Surface Treatment Haze 3% | Life Time (Typ.) 50,000 hrs |
| Operation Hours 24 Hrs | Orientation Landscape & Portrait |

⊖ CONNECTIVITY

| | |
|--|----------------------------|
| Input HDMI, DP, DVI-D, RGB, Audio, USB 2.0 | Output DP, Audio |
| External Control RS232C In/out, RJ45 (LAN) In, IR In | |

⊖ MECHANICAL SPECIFICATION

| | |
|---|---|
| Bezel Colour Black | Bezel Width 2.3 mm (T/L), 1.2 mm (B/R) |
| Monitor Dimension (W x H x D) 1,077.6 x 607.8 x 89.7 mm | Weight (Head) 17.8 kg |
| Carton Dimensions (W x H x D) 1,214 x 778 x 263 mm | Packed Weight 22.8 kg |
| Handle Yes | VESA™ Standard Mount Interface 600 x 400 mm |

⊖ KEY FEATURE

KEY FEATURE

Temperature Sensor, Tile Mode (Up to 15x15), Natural Mode@Tile Mode, ISM Method, DPM Select, Smart Energy Saving, USB Cloning, Easy Brightness Control, Contents Scheduling (USB), Calibration Mode, Sync Mode, PM Mode, HDMI-CEC1), Wake on LAN, OSD Portrait Mode, Fail Over, No Signal Image, OPS Power Control, Scan Inversion (with Pivot Mode)

⊖ ENVIRONMENT CONDITIONS

| | |
|---|---|
| Operation Temperature 0 °C to 40 °C | Operation Humidity 10% to 80% |
|---|---|

⊖ POWER

| | |
|--|--|
| Power Supply 100-240V~, 50/60Hz | Power Type Built-in Power |
| Power Consumption - Typ. 90 W | Power Consumption - Max. 110 W |
| Power Consumption - Smart Energy Saving 55 W | |

⊖ Certification

| | |
|---|---|
| Safety AS/NZS 60950,CB Scheme | EMC AS/NZS CISPR32,RCM(Class A) |
| ErP / Energy Star N/A / Yes (Energy Star 7.0) | |

⊖ Media Player Compatibility

| | |
|----------------------------------|--|
| OPS Type Compatible No | External Media Player Attachable Yes (MP500 / MP700) |
|----------------------------------|--|

⊖ Software Compatibility

| | |
|---|--|
| Content Management Software SuperSign CMS | Control and Monitoring Software SuperSign Control/Control+ |
|---|--|

⊖ ACCESSORIES

| | |
|--|---|
| Basic Remote Controller, Power Cord, RS232C Cable, LAN Cable, DP Cable, IR Receiver, Guide Bracket, Screws, Manual | Optional Wall Mount (Landscape: WM-L640V, Portrait: WM-P640V) |
|--|---|