



SPECIFICATIONS

| | |
|------------------------------------|---|
| Model Name | GeForce RTX™ 4060 Ti GAMING X 16G |
| Cores | 4352 Units |
| Memory | 16GB GDDR6 |
| Standard sběrnice | PCI Express® Gen 4 x16 (uses x8) |
| Rozhraní paměti | 128-bit |
| Takt jádra (MHz) | Extreme Performance: 2655 MHz (MSI Center) Boost: 2640 MHz |
| Takt paměti (MHz) | 18 Gbps |
| Max připojených displejů | 4 |
| Output | DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR and 8K@60Hz HDR and Variable Refresh Rate (VRR) as specified in HDMI™ 2.1a) |
| HDCP podpora | Y |
| Digital Maximum Resolution | 7680 x 4320 |
| Doporučený výkon zdroje (W) | 550 W |
| Napájecí kabely | 8-pin x 1 |
| Podpora DirectX verze | 12 Ultimate |
| Podpora OpenGL verze | 4.6 |
| Rozměry (mm) | 247 x 130 x 42 mm |
| Váha (g) | 672 g / 1089 g |

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



TWIN FROZR 9

MSI's TWIN FROZR 9 thermal design enhances heat dissipation all around the graphics card.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Copper Baseplate

A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Airflow Control

Don't sweat it, Airflow Control guides the air to exactly where it needs to be for maximum cooling.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.