





Powered by AC or DC:

**AC via AC adapter** DC via 12Vmax, 14.4V, 18V Li-ion battery







# **High Quality Sound Radio**

With midrange / treble speakers and woofer for deeper and richer sound



equipped with Bluetooth class 2\*\* to wirelessly play music from a mobile device. \*\*With a range of 10m (33ft); up to 30m (100ft) in good radio conditions

#### 7 Selectable sound modes

- Sound mode can be selected to suit the music genre.
- MY EQ (my equalizer) mode enables to independently adjust treble, midrange and bass for a desired sound quality.
- LED color indicates the selected sound mode.

Equalizer	LED
FLAT	White
JAZZ	Blue
ROCK	Red
CLASSIC	Brown
РОР	Pink
NEWS	Yellow
MY EQ	Green





### Carry handle with built in FM antenna

- Swivels 90 degrees
- Features soft grip

## Dust and shower-proof construction: IP65

For use in outdoor applications or harsh environments



#### **USB** output port

- · allows for charging a mobile device.
- Type A USB socket for DC5V/ 2.4A USB output



#### **AUX-IN jack**

used as a stereo speaker by connecting to external audio source with a commercial connecting cable.



### **Dual Power Sources**

Runs on AC adapter or Makita rechargeable Li-ion batteries.



#### Continuous run time (approx): hour

On a single full battery charge

	BL1016 (1.5Ah)	5.5	14.4V	BL1415	N(1.5Ah)	4.5		BL1815N(1.5Ah)	5.0
2V ax				BL1430B(3.0Ah)		8.0	3.0	BL1820B(2.0Ah)	6.5
	BL1021B(2.0Ah)	7.0		RI 1440	(4 0 4 h)		18V	BL1830B(3.0Ah)	9.0
							100	BL1840B(4.0Ah)	13
	BL1041B(4.0Ah)	14		BL1450	(5.0Ah)			BL1850B(5.0Ah)	16
				BL1460E	3(6.0Ah)	16		BL1860B(6.0Ah)	20
Job Site Radio DMR115 12V max-18 V / AC									
reg	uency Band	FM/D	AB / DAB-	+: 87.5 - 10	8 MHz / 174	4.928 - 2	39.200 MI	Hz / 174.928 - 239.200	MHz

Job Site Rad	IO DIVIRT 15 12V max-18 V / AC					
Frequency Band	FM / DAB / DAB+: 87.5 - 108 MHz / 174.928 - 239.200 MHz / 174.928 - 239.200 MHz					
Speaker Size	Sides: Ø63.5 mm x2					
•	Bottom: Ø101.6 mm					
Max Output	18 V: 5 W x2 +25 W / 14.4 V: 3 W x2 +15 W / 12V max: 2 W x2 +10 W					
Bluetooth	Version: 5.0					
	Profile: A2DP / SCMS-T / AVRCP					
	Supported Codec: SBC / AAC					
	Max Transmission Range (Optimum): 10 m (33 ft) Transmission Power Class: 2					
	Compatible Bluetooth Profile: A2DP					
Dimensions (L x W x H)	ons (L x W x H) w/ Handle in Retracted Position: 268x164x295 mm (10-1/2"x6-1/2"x11-5/8")					
	w/ Handle in Upright Position: 268x164x437 mm (10-1/2"x6-1/2"x17-1/4")					
Net weight*	5.0 - 5.5 kg (11.1 - 12.1 lbs.)					
	*with out battery 4.8kg (10.0 lbs.)					
Standard Equipment : A	C Adaptor					

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area

### Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan